

قاتل الإطارات الصلب المسطح سواء فوق أو تحت الأرض

Flat Type Mechanical Tire Killers Please Specify: Below or Above the Ground:

Model	Teeth Material Type	Teeth Thick-ness	Number of Bearing Installed	Number of Springs Installed	Max Load Capacity	Teeth Height Above Plate	Length Per Tire Killer	Width Per Tire Killer	Top Plate Thick-ness	One Year War-ranty	Max Driving Speed	Price SR/Dhs
ZSF-TK1001-C	Stainless Steel	10.0 mm	2	2	10 tons	70 mm	1.09 m	420 mm	5 mm	YES	3km/hr	3,856

Note : Installation cost (Jeddah Region) 690 SR/Dhs per linear meter (Includes concrete base 20cmx 60cm and fixing of tire killer).

Note : Installation cost (Jeddah Region) 390 SR/Dhs per linear meter on Existing Concrete Base



Shipping Weight

Above Ground	
Model	Weight
ZSF-TK1001-A	75+5
ZSF-TK1001-B	76+5
ZSF-TK1001-C	77+5
ZSF-TK1001-D	90+5

1 Year Warranty

Customer must perform the following for warranty to be in effect.

1. Open and remove Debris and clean weekly the tire killer.
2. Blow air around Spring & Ball Bearing weekly.
3. Spray WD40 around Ball Bearing weekly.
4. Assemble and test weekly.
5. Customer must bring to SOFAB Factory the Damaged Parts for repair or replacement.
6. SOFAB technical team will not come to site for repair.

